
## Gazelle 5.4.x Web Services Configuration


#### Assumptions

- You have already reviewed the more general documentation:
  - Gazelle Configuration: Entering Your Parameters
- So, you have the big picture
- You just want to learn about Web Service configuration

#### Start Here


• Under Configurations, select "Systems Configuration"






#### Select the System to Configure

#### Configurations



#### Select the Type of Service to Configure


- You can use the filter to select Webservice configurations
- You could also filter by Actor if that is easier for you



#### Review by Transaction: In this example, ITI-42

Actor ≑	Host name ≑	IP ≑	Port	is Secured ? ≑	WSType	URL	Approved	Actio	on		
DOC_REGISTRY - Document Registry	records0	~	8080 🔒	v <b>&gt;</b>	ITI-42:Register.b:r.b	https://records0:8080/your_url	🛑 no	~	<b>"</b>	ළු	
DOC_REGISTRY - Document Registry	records0	~	8080 🔒	$\checkmark$	ITI-61:Register On-Demand Doc:rod.b	https://records0:8080/your_url	🛑 no	*	<b>1</b>	ආ	Û
DOC_REGISTRY - Document Registry	records0	~	80		ITI-42:Register.b:r.b	http://records0/your_url	🛑 no	~	<i>.</i>	ආ	Ē
DOC_REGISTRY - Document Registry	records0	~	80		ITI-61:Register On-Demand Doc:rod.b	http://records0/your_url	🛑 no	*	<b>"</b>	ආ	Û
DOC_REGISTRY - Document Registry	records0	~	80		ITI-18:Stored Query:sq.b	http://records0/your_url	🛑 no	~	<b>"</b>	ආ	
DOC_REGISTRY - Document Registry	records0	~	8080 🔒		ITI-18:Stored Query:sq.b	https://records0:8080/your_url	🛑 no	~	ø	ආ	Ē

#### Select the Pencil Icon (Edit)



#### Make changes as needed

- This is a TLS connection, so you are editing the secure port
- You need to add the suffix for your URL. The default we generate is "your\_url"
- Save, and move on to the unsecured version.

Port Secure	4 *
	u
8080	
JRL suffix *	
your_url	


#### For The Unsecured Endpoint

- The caption just says "Port", so this is the non-secure port
- When you enter the URL suffix:
  - You can duplicate the value for the secure port, or
  - You can use a different suffix
- Save, and move on to the next transaction.

Type of configuration
Webservice
WebService Type *
ITI-42:Register.b:r.b
Port *
80
URL suffix *
your_url
The final address will be : http://records0/your_url Save Last changed : 9/26/16 9:05:41 AM (GMT-06:00) by Automate

#### You Want Your Repository on a Separate Host: First, Add Another Host

Network Configuration Page



Edit configuration for Pu	blic Records
Host name: records3	
External host (ignoring domain name)	The alias will show up in DNS as a second name for this host. The name records3 is fixed.
P AddressYour IP is currently empty; it will be Comment	assigned later by a gazelle admin
Save	

#### Change the Host on the Main Configuration Page

	Actor	(4) DOC_RE	POSITORY - Doo	cument Re	pository	• × 0	
Export as Exe Type	cel file Actor ≑		Host name ≑	IP 🖨	Port	is Secured ? ≑	Details 1
Webservice	DOC_REPOSITORY Repository	- Document	records0 PleaseSelect	~	80		ITI-41:Provide and Register.b:pr.b
Webservice	DOC_REPOSITORY Repository	- Document	records3 records0		<mark>⊖</mark> 8080	$\checkmark$	ITI-41:Provide and Register.b:pr.b
Webservice	DOC_REPOSITORY Repository	- Document	records0	~	80		ITI-43:Retrieve.b:ret.b
Webservice	DOC_REPOSITORY Repository	- Document	records0	~	<mark>⊖</mark> 8080		ITI-43:Retrieve.b:ret.b

# Or, Change the Host on the Detailed Configuration Form

system for a	is configuration			
XDSb_REP	Records (1)			<b>,</b>
Actor				
DOC_REP	OSITORY-Document F	epository		
Host name *	-			
records3				
PleaseSel	ct			
records3				
records0			 	
Approved Comment Type of conf	guration			

#### Important Final Step

### Approve Configurations for your Systems

- Use individual check mark icons, or
- Use "Approve all" button
- Signal your partners that you are done

